

## DECLARATION OF PERFORMANCE

DOP# SSETA-8100



### SENCO Staples N, Q, S & SP 12 $\mu$ m Zinc, with Type 3 coating.

Product type, intended use/ uses and identification of the construction product	
Generic type	Dowel-type fastener with resin coating
Intended use	Load-bearing connections in wooden structures for withdrawal and shear loads in short, medium, long-term, and permanent duration.
Unique Identification	SSETA-8100
Wire material	Non-alloy steel acc. EN 16120 with deformed circular cross-section
ETA 21/0078 issued by	DIBT
On the basis of technical specification	EAD 130019-00-0603
AVCP System	3
Notified body	1503

Declared performances						
Essential Characteristics			Performance			
Type			N	Q	S	SP
$d$	Nominal diameter	[mm]	1,54	1,80	2,03	2,03
$b$	Width of staple crown	[mm]	10,6	11,26	11,8	27
$l$	Length	[mm]	28 – 100	32 – 115	36 – 172	36 - 172
$t_3$	Minimum coated length	[mm]	$\geq 0,5 \times l$			
$M_{y,k} (M_{y,Rk})$	Characteristic Yield Moment (1 staple leg)	[Nm]	0,72	0,94	1,56	1,56
$f_{ax,k}$	Characteristic Withdrawal parameter, short & medium term loads <sup>1)</sup>	[N/mm <sup>2</sup> ]	4,91	4,97	5,54	5,54
$R_{ax,d}$	Design value of withdrawal under long-term & permanent loads <sup>1)</sup>	N	70			
$f_{head,k}$	Characteristic head pull-through parameter <sup>1)</sup>	[N/mm <sup>2</sup> ]	41	32	29	39
$f_{head,k}$	Characteristic head pull-through parameter for wood fiber insulation <sup>2)</sup>		-	-	-	9,36
$f_u$	Minimum tensile strength of wire	[N/mm <sup>2</sup> ]	900			
Reaction to fire			A1			
Durability against corrosion			Zinc Plated 12 $\mu$ m, Service Class 1 & 2 acc. Eurocode 1992-1-1			
Durability of type 3 coating			Compliant with EAD 130019-00-0603: 2.2.9 $f_{ax,k} \geq 4,9 \text{ N/mm}^2$			

<sup>1)</sup>  $\rho_K \geq 350 \text{ kg/m}^3$

<sup>2)</sup> Mean density  $\geq 200 \text{ kg/m}^3$  with  $t_{1,\min} \geq 60 \text{ mm}$

## DECLARATION OF PERFORMANCE

DOP# SSETA-8100



Declared performances (continued)						
Essential Characteristics			Performance			
Type		[mm]	N	Q	S	SP
$t_{1,max}$	Maximum thickness: Solid wood of soft wood ( $\rho_k \leq 400 \text{ kg/m}^3$ )	[mm]	80			
$t_{1,max}$	Maximum thickness: Wood-based panels and hard- and softwood ( $400 < \rho_k \leq 650 \text{ kg/m}^3$ )	[mm]	60			
$t_{1,max}$	Maximum thickness: Wood-based panels and gypsum boards ( $650 < \rho_k \leq 900 \text{ kg/m}^3$ )	[mm]	40			
$t_{1,max}$	Maximum thickness: Hard-boards, gypsum fiberboards, cement bonded particle board ( $650 < \rho_k \leq 900 \text{ kg/m}^3$ )	[mm]	25			
$t_{1,max}$	Maximum thickness: Highly compressed gypsum fiberboards ( $1200 < \rho_k \leq 1600 \text{ kg/m}^3$ )	[mm]	20			
$t_{1,min}$	Minimum thickness of solid timber (softwood) <sup>2) 3)</sup>	[mm]	24			
$t_{1,min}$	Minimum thickness of Solid Wood Panels <sup>2) 3)</sup>	[mm]	10,78	12,60	14,21	14,21
$t_{1,min}$	Minimum thickness of Plywood <sup>2) 3)</sup>	[mm]	6			
$t_{1,min}$	Minimum thickness of Oriented Strand Boards OSB <sup>2) 3)</sup>	[mm]	8			
$t_{1,min}$	Minimum thickness of Resin-bonded particleboards <sup>2) 3)</sup>	[mm]	8			
$t_{1,min}$	Minimum thickness of Cement-bonded particleboards <sup>2) 3)</sup>	[mm]	8			

<sup>2)</sup>  $\rho_k \geq 350 \text{ kg/m}^3$

<sup>3)</sup> If the staple crown is countersunk into material:  $t_{1,min}$  must be increased with 2 mm.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of Kyocera Senco Netherlands B.V by:

Place and date of issue: Lelystad, 03-01-2022



Lars Aa. Mortensen  
Technical Manager, KYOCERA Senco EMEA