

## PRODUCT IDENTIFICATION

Following articles which are sold in the brand name Senco are covered by this Declaration of Performance:

Article number

<b>BJ25APBF</b>	<b>BJ27APBF</b>
<b>BJ21AABF</b>	<b>BJ21APBF</b>
<b>BJ25AABF</b>	<b>BJ22APBF</b>



The manufacturer declares for:

### Round cross-section ring shank nail, diameter 2,5 mm up to 75 mm

Product is in accordance with EN 14592:2008 + A1:2012 "Timber Structures - Dowel-type fasteners - Requirements"

Initial Type Testing was performed to confirm essential characteristic values in accordance to table ZA.1 in EN 14592:2008 + A1:2012. Declared values accompanies with the CE mark in this technical document.

Initial Type Testing is performed by notified body: **1686**

For this product the compliance with the conditions of the Annex ZA in EN 14592 are accomplished.



Treatment:

- Bright Basic - Service Class 1
- Electro galvanized - Service Class 1
- Electro galvanized 12 µm - Service Class 1,2
- Hot dipped galvanized 55 µm - Service Class 1, 2, 3
- Stainless Steel A2 - Service Class 1, 2, 3

## Dimensions

<b>Bright Basic</b>				
<b>Length</b>	<b>Diameter (mm)</b>	<b>Shank type</b>	<b>Length of threaded part (mm)</b>	<b>Length of point (mm)</b>
50mm	2,5	Ring	NA	3,6
55mm				
65mm				
75mm				
<b>Electro galvanized / Electro galvanized 12 µm</b>				
<b>Length</b>	<b>Diameter (mm)</b>	<b>Shank type</b>	<b>Length of threaded part (mm)</b>	<b>Length of point (mm)</b>
50mm	2,5	Ring	NA	3,6
65mm				

## Mechanical strenght and stiffness

<b>Bright Basic</b>						
Length	Characteristic yield moment (Nmm)	Characteristic withdrawal parameter (N/mm <sup>2</sup> )*,**	Characteristic head pull through parameter (N/mm <sup>2</sup> )	Characteristic tensile strenght (N/mm <sup>2</sup> )	Coating length (mm)	Head cross sectional (mm <sup>2</sup> )
50mm	1575	7,18	22,45	629	37,5	27
55mm					40,5	
65mm					49,5	
75mm					55,5	
<b>Electro galvanized / Electro galvanized 12 µm</b>						
Length	Characteristic yield moment (Nmm)	Characteristic withdrawal parameter (N/mm <sup>2</sup> )*,**	Characteristic head pull through parameter (N/mm <sup>2</sup> )	Characteristic tensile strenght (N/mm <sup>2</sup> )	Coating length (mm)	Head cross sectional (mm <sup>2</sup> )
50mm	1575	7,18	22,45	629	37,5	27
65mm					49,5	

\* The withdrawal parameter  $f_{ax,k}$  is tested in wood with characteristic density of  $\rho_k=350\text{kg/m}^3$

\*\* Coating type 3

System of assessment and verification of constancy of performance for timber fasteners used for structural products is 3.

A Factory Production Control system is established and maintained under responsibilities of the manufacturer:

Name and contact address of the manufacturer

**Verpa Senco B.V.**


**Pascallaan 88**

**8218 NJ Lelystad, The Netherlands**

This declaration of performance is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

June 30, 2013

Lelystad, The Netherlands



Fred van Gerven,  
Technical Manager

Document no: VS-CPR-201305-S040